

## Specification Sheet

Part Number: S2HM25HIRHSH1



2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg

**Article Number**

151-29403

**Type**

S2HM25

**Color**

Black (BK)

### Features & Benefits

- Separates bundles from wear and chafing, providing additional longevity.
- Hexagonal retention feature (S2HM25) captures a bolt or nut requiring tool access from the back side only. •A socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt (S2CM25.)
- Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.

**Quantity Per**

bag

### Product Description

HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, the H-profile on the saddle mount provides a tight circumferential loop on large and small bundles. Cable ties up to 1/2" wide are used to secure the bundles.

<b>Short Description</b>	2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg
<b>Global Part Name</b>	S2HM25-PA66HIRHSUV-BK
<b>Length L (Imperial)</b>	1.80
<b>Length L (Metric)</b>	45.0
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	1.2
<b>Width W (Metric)</b>	30.0
<b>Cable Ties</b>	T50 - T250
<b>Height H (Imperial)</b>	0.90
<b>Height H (Metric)</b>	23.0
<b>Cable Tie Width Max (Imperial)</b>	0.5
<b>Cable Tie Width Max (Metric)</b>	12.7
<b>Mounting Hole Diameter D (Imperial)</b>	0.24
<b>Mounting Hole Diameter D (Metric)</b>	6.0 mm 6.35 mm (hexagonal)
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.24
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.24

**Mounting Hole Diameter D Max (Metric)**

6.0

**Stud Diameter (Metric)**

6.35 mm

**Stud Diameter (Imperial)**

0.25

**Material**

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut**

PA66HIRHSUV

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +230°F (-40°C to +110°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

500

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

9.88

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)