

Specification Sheet

Part Number: S2HM250HIRHSH1

Separates bundles from wear and chafing, providing additional longevity.

Hexagonal retention feature (S2HM25) captures a bolt or nut requiring tool access from the back side only.

A socket counterbore allows securing with a socket wrench from the top side for use with a weld stud or bolt (S2CM25.)

Made from impact modified, heat stabilized, UV resistant material making it ideal for heavy duty applications.



2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg

Article Number 151-29403

Type S2HM25

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's saddle mount can be installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate them and prevent chafing and wear. Fastened to a frame rail or mounting bracket, the H-profile on the saddle mount provides a tight circumferential loop on large and small bundles. Cable ties up to 1/2" wide are used to secure the bundles.

| | |
|-------------------------------------|--|
| Short Description | 2-Way Saddle Mount, 3.5" Max Bundle Diameter, 0.25" Stud Diameter, PA66HIRHSUV, Black, 500/pkg |
| Global Part Name | S2HM25-PA66HIRHSUV-BK |
| Length L (Imperial) | 1.80 |
| Length L (Metric) | 45.0 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 1.2 |
| Width W (Metric) | 30.0 |
| Bundle Diameter Max (Imperial) | 3.5 |
| Bundle Diameter Max (Metric) | 89.0 |
| Cable Ties | T50 - T250 |
| Height H (Imperial) | 0.90 |
| Height H (Metric) | 23.0 |
| Cable Tie Width Max (Imperial) | 0.5 |
| Cable Tie Width Max (Metric) | 13.5 |
| Mounting Hole Diameter D (Imperial) | 0.24 ";0.25 (hexagonal) |
| Mounting Hole Diameter D (Metric) | 6.0 mm 6.35 mm (hexagonal) |

| | |
|---|--|
| Mounting Hole Diameter D Min (Imperial) | 0.24 |
| Mounting Hole Diameter D Max (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Metric) | 6.0 |
| Stud Diameter (Metric) | 6.35 mm |
| Stud Diameter (Imperial) | 0.25 |
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |

Customs Number

3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)