

Specification Sheet

Part Number: S3STM500HIRHSF1



Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08 - 0.52", PA66HIRHSUV, Black, 250/pkg

Article Number	151-29501
Type	S3STM50
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Heavy duty fir tree mount requires low insertion force and high extraction force.•Impact modified, heat stabilized, UV material makes it ideal for heavy-duty solutions.
Quantity Per	bag

Product Description

The saddle mount acts as a standoff, elevating bundles above bolt protrusions commonly found in frame rails and panels. A tension tab on the mount allows cable ties to be pre-assembled in a ready position prior to bundles being brought to the mount. The mount can secure up to four separate bundles, providing parallel spacing between the frame rail and adjacent bundles. Fir tree eliminates the need for mounting hardware. For use with HellermannTyton T50-T255 ties.

Short Description	Fir Tree Saddle Mount, Hole Diameter 0.5", Panel Thickness 0.08 - 0.52", PA66HIRHSUV, Black, 250/pkg
--------------------------	--

Global Part Name	S3STM50-PA66HIRHSUV-BK
-------------------------	------------------------

Length L (Imperial)	2.0
----------------------------	-----

Length L (Metric)	50.0
--------------------------	------

Fixation Method	with Fir Tree (Mounts)
------------------------	------------------------

Width W (Imperial)	0.9
---------------------------	-----

Width W (Metric)	22.0
-------------------------	------

Bundle Diameter Min (Imperial)	5.0
---------------------------------------	-----

Bundle Diameter Min (Metric)	127.0
-------------------------------------	-------

Bundle Diameter Max (Imperial)	5.0
---------------------------------------	-----

Bundle Diameter Max (Metric)	127.0
-------------------------------------	-------

Bundle Diameter 1st Loop Max (Imperial)	5.0
--	-----

Bundle Diameter 1st Loop Max (Metric)	127.0
--	-------

Bundle Diameter 2nd Loop Max (Imperial)	5.0
--	-----

Bundle Diameter 2nd Loop Max (Metric)	127.0
--	-------

Height H (Imperial)	1.40
----------------------------	------

Height H (Metric)	35.0
Panel Thickness Min(Imperial)	0.07
Panel Thickness Max(Imperial)	0.51
Panel Thickness Min (Metric)	1.9
Panel Thickness Max (Metric)	13.0
Mounting Hole Diameter D (Imperial)	0.50
Mounting Hole Diameter D (Metric)	12.7 - 13.7 mm
Mounting Hole Diameter D Min (Imperial)	0.50
Mounting Hole Diameter D Max (Imperial)	0.54
Mounting Hole Diameter D Max (Metric)	13.7
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Minimum Extraction Force (Imperial)	200.0
Minimum Extraction Force (Metric)	890

ROHS Complaint

Yes

Package Quantity(Imperial)

250

Package Quantity (Metric)

250

Customs Number

3926909987