

## Specification Sheet

Part Number: MMB00C2



Masonry Cable Tie Mount, 1.185" Long, .188" Hole Dia, .18" Max Cable Tie Width, PA66STHS,Black,100/pkg

**Article Number** 151-29800

**Type** MMB0

**Color** Black (BK)

**Features & Benefits**

- Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.
- The mounts have easy installation into predrilled holes allowing for faster use.

**Quantity Per** bag

**Product Description**

HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.

<b>Short Description</b>	Masonry Cable Tie Mount, 1.185" Long, .188" Hole Dia, .18" Max Cable Tie Width, PA66STHS,Black,100/pkg
<b>Global Part Name</b>	MMB0-PA66STHS-BK
<b>Length L (Imperial)</b>	1.185
<b>Length L (Metric)</b>	30.1
<b>Fixation Method</b>	with Fir Tree (Mounts)
<b>Width W (Imperial)</b>	0.355
<b>Width W (Metric)</b>	9.0
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.35
<b>Height H (Metric)</b>	8.90
<b>Cable Tie Width Max (Imperial)</b>	0.18
<b>Cable Tie Width Max (Metric)</b>	4.6
<b>Mounting Hole Diameter D (Imperial)</b>	0.188
<b>Mounting Hole Diameter D (Metric)</b>	4.7 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	4.7

<b>Material</b>	Polyamide 6.6, super tough, heat stabilized (PA66STHS)
<b>Material Shortcut</b>	PA66STHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988