

## Specification Sheet

Part Number: MMB.50M4



Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg

**Article Number** 151-30001

**Type** MMB.5

**Color** Black (BK)

**Features & Benefits**

- Masonry Mounts provide a permanent solution when fastening wire and cables to masonry surfaces.
- The mounts have easy installation into predrilled holes allowing for faster use.

**Quantity Per** bag

**Product Description**

HellermannTyton Masonry Mounts provide a permanent method of attaching wire and cable to masonry surfaces. Masonry mounts simply tap into predrilled holes and can be used for indoor and outdoor applications.

<b>Short Description</b>	Masonry Cable Tie Mount, 1.24"L, .25" Hole Dia, .18" Max Cable Tie Width, PA66STHS, Black, 1000/pkg
<b>Global Part Name</b>	MMB.5-PA66STHS-BK
<b>Length L (Imperial)</b>	1.24
<b>Length L (Metric)</b>	31.5
<b>Fixation Method</b>	with Fir Tree (Mounts)
<b>Width W (Imperial)</b>	0.375
<b>Width W (Metric)</b>	9.5
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.37
<b>Height H (Metric)</b>	9.40
<b>Cable Tie Width Max (Imperial)</b>	0.18
<b>Cable Tie Width Max (Metric)</b>	4.6
<b>Mounting Hole Diameter D (Imperial)</b>	0.25
<b>Mounting Hole Diameter D (Metric)</b>	6.35 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	6.35

<b>Material</b>	Polyamide 6.6, super tough, heat stabilized (PA66STHS)
<b>Material Shortcut</b>	PA66STHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>Use Conditions</b>	For Indoor Use Only
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988