

## Specification Sheet

Part Number: CTAP210C2



Cable Tie Anchor Mount, .20 x.70" Hole Dia, .20" Max Tie Width, PA66, White, 100/pkg

**Article Number** 151-30200

**Type** CTAP2

**Color** White (WH)

**Features & Benefits**

- Mount provides a "stand-off" for perpendicular bundles.
- Secures with a single screw with the option of an additional screw, providing extra stability.

**Quantity Per** bag

**Product Description**

HellermannTyton cable tie anchor plates are designed as a "stand-off" mount for perpendicular wire bundles. These mounts offer an elongated mounting hole for easier alignment of wire bundles. The mounts are installed quick and easy by securing a single screw, with the option of an additional screw for maximum stability.

<b>Short Description</b>	Cable Tie Anchor Mount, .20 x.70" Hole Dia, .20" Max Tie Width, PA66, White, 100/pkg
<b>Global Part Name</b>	CTAP2-PA66-WH
<b>Length L (Imperial)</b>	2.13
<b>Length L (Metric)</b>	54.1
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.5
<b>Width W (Metric)</b>	12.7
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.14
<b>Height H (Metric)</b>	3.50
<b>Cable Tie Width Max (Imperial)</b>	0.2
<b>Cable Tie Width Max (Metric)</b>	5.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.2 x 0.7
<b>Mounting Hole Diameter D (Metric)</b>	5.0 x 19.0 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	19.0

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	1.994