

Specification Sheet

Part Number: CTM00C2



KR/CTM series are designed to provide stability to wire bundles. These mounts can accommodate miniature, intermediate, or standard cross-section cable ties.

Each mount is secured with a single screw.

Cable Tie Anchor Mount, 0.58 x .37", 0.15" Hole Dia, 0.2" Max Tie Width, PA66, Black, 100/pkg

| | |
|---------------------|---|
| Article Number | 151-30300 |
| Type | CTM0 |
| Color | Black (BK) |
| Quantity Per | bag |
| Product Description | Designed specifically for holding heavier cable bundles these mounting bases can be used in many industries from agriculture to truck manufacture. They offer a very secure fixing and can be used with a wide variety of heavy duty cable ties up to 8.3 mm width. |
| Short Description | Cable Tie Anchor Mount, 0.58 x .37", 0.15" Hole Dia, 0.2" Max Tie Width, PA66, Black, 100/pkg |
| Global Part Name | CTM0-PA66-BK |

| | |
|---------------------------------------|----------------------|
| Length L (Imperial) | 0.58 |
| Length L (Metric) | 14.7 |
| Fixation Method | Screw Mount |
| Width W (Imperial) | 0.37 |
| Width W (Metric) | 9.4 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | 0.27 |
| Height H (Metric) | 6.90 |
| Cable Tie Width Max (Imperial) | 0.2 |
| Cable Tie Width Max (Metric) | 5.0 |
| Mounting Hole Diameter D (Imperial) | 0.15 |
| Mounting Hole Diameter D (Metric) | 3.8 mm |
| Mounting Hole Diameter D Max (Metric) | 3.8 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |

| | |
|-------------------------------|--|
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL ANSI/UL 62275 UL ANSI/UL 1565 UL ANSI/UL 746B |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

