

## Specification Sheet

Part Number: CTM010C2



KR/CTM series are designed to provide stability to wire bundles. These mounts can accommodate miniature, intermediate, or standard cross-section cable ties.

Each mount is secured with a single screw.

Cable Tie Anchor Mount, .58" x .37", .15" Hole Dia, .2" Max Tie Width, PA66, White, 100/pkg

Article Number 151-30303

Type CTM0

Color White (WH)

Quantity Per bag

Product Description HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.

Short Description Cable Tie Anchor Mount, .58" x .37", .15" Hole Dia, .2" Max Tie Width, PA66, White, 100/pkg

Global Part Name CTM0-PA66-WH

|                                       |                          |
|---------------------------------------|--------------------------|
| Length L (Imperial)                   | 0.58                     |
| Length L (Metric)                     | 14.7                     |
| Fixation Method                       | Screw Mounting and Rivet |
| Width W (Imperial)                    | 0.37                     |
| Width W (Metric)                      | 9.4                      |
| Cable Ties                            | T18 - T50                |
| Height H (Imperial)                   | .27                      |
| Height H (Metric)                     | 6.90                     |
| Cable Tie Width Max (Imperial)        | 0.2                      |
| Cable Tie Width Max (Metric)          | 5.0                      |
| Mounting Hole Diameter D (Imperial)   | 0.15                     |
| Mounting Hole Diameter D (Metric)     | 3.8 mm                   |
| Mounting Hole Diameter D Max (Metric) | 3.8                      |
| Material                              | Polyamide 6.6 (PA66)     |

|                               |  |
|-------------------------------|--|
| Material Shortcut             | PA66   |
| Flammability                  | UL 94 V-2  |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C)                       |
| Reach Compliant (Article 33)  | Yes  |
| ROHS Compliant                | Yes  |
| Certification/Specification   | UL   ANSI/UL 1565 UL   ANSI/UL 62275 UL   ANSI/UL 746B |
| UL Recognized (US)            | Yes  |
| UL Recognized (US and Canada) | Yes  |
| Package Quantity (Imperial)   | 100  |
| Package Quantity (Metric)     | 100  |
| Customs Number                | 3926909988   |