

## Specification Sheet

Part Number: CTM110M4



Cable Tie Anchor Mount, .58" x .37", .19" Hole Dia, .2" Max Tie Width, PA66, White, 1000/pkg

**Article Number** 151-30406

**Type** CTM1

**Color** White (WH)

**Features & Benefits**

- Designed for use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Secures with a single screw providing quick installation.

**Quantity Per** bag

**Product Description** HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.

<b>Short Description</b>	Cable Tie Anchor Mount, .58" x .37", .19" Hole Dia, .2" Max Tie Width, PA66, White, 1000/pkg
<b>Global Part Name</b>	CTM1-PA66-WH
<b>Length L (Imperial)</b>	0.58
<b>Length L (Metric)</b>	14.7
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.37
<b>Width W (Metric)</b>	9.4
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.27
<b>Height H (Metric)</b>	6.90
<b>Cable Tie Width Max (Imperial)</b>	0.2
<b>Cable Tie Width Max (Metric)</b>	5.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.19
<b>Mounting Hole Diameter D (Metric)</b>	4.8 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	4.8

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL 62275
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988