

Specification Sheet

Part Number: CTM310C2



Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 100/pkg

| | |
|--------------------------------|---|
| Article Number | 151-30605 |
| Type | CTM3 |
| Color | White (WH) |
| Features & Benefits | <ul style="list-style-type: none">• Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles.• Secures with a single screw providing quick installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw. |

| | |
|--|---|
| Short Description | Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 100/pkg |
| Global Part Name | CTM3-PA66-WH |
| Length L (Imperial) | 0.86 |
| Length L (Metric) | 21.8 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.61 |
| Width W (Metric) | 15.5 |
| Cable Ties | T18 - T120 |
| Height H (Imperial) | .37 |
| Height H (Metric) | 9.40 |
| Cable Tie Width Max (Imperial) | 0.31 |
| Cable Tie Width Max (Metric) | 7.9 |
| Mounting Hole Diameter D (Imperial) | 0.2 |
| Mounting Hole Diameter D (Metric) | 5.1 mm |
| Mounting Hole Diameter D Max (Metric) | 5.1 |

| | |
|--|--|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL ANSI/UL 62275 UL ANSI/UL 1565 UL ANSI/UL 746B |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |
| Content Unit(BMEcat) | pcs. |

