

Specification Sheet

Part Number: CTM310M4



Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 1000/pkg

Article Number 151-30607

Type CTM3

Color White (WH)

Features & Benefits

- Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles.
- Secures with a single screw providing quick installation.

Quantity Per bag

Product Description HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.

| | |
|--|--|
| Short Description | Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 1000/pkg |
| Global Part Name | CTM3-PA66-WH |
| Length L (Imperial) | 0.86 |
| Length L (Metric) | 21.8 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.61 |
| Width W (Metric) | 15.5 |
| Cable Ties | T18 - T120 |
| Height H (Imperial) | .37 |
| Height H (Metric) | 9.40 |
| Cable Tie Width Max (Imperial) | 0.31 |
| Cable Tie Width Max (Metric) | 7.9 |
| Mounting Hole Diameter D (Imperial) | 0.2 |
| Mounting Hole Diameter D (Metric) | 5.1 mm |
| Mounting Hole Diameter D Max (Metric) | 5.1 |

| | |
|--|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL 62275 |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity(Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |