

## Specification Sheet

Part Number: TM1SF0C2



Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg

**Article Number** 151-40100

**Type** TM1SF

**Color** Black (BK)

**Features & Benefits**

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution.
- The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Quantity Per** bag

**Product Description**

HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

<b>Short Description</b>	Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Black, 100/pkg
<b>Global Part Name</b>	TM1SF-PA66-BK
<b>Length L (Imperial)</b>	0.62
<b>Length L (Metric)</b>	15.75
<b>Fixation Method</b>	with Arrowhead / Push Mount (Mounts)
<b>Width W (Imperial)</b>	0.4
<b>Width W (Metric)</b>	10.2
<b>Cable Ties</b>	T18 - T50
<b>Height H (Imperial)</b>	.18
<b>Height H (Metric)</b>	4.60
<b>Cable Tie Width Max (Imperial)</b>	0.2
<b>Cable Tie Width Max (Metric)</b>	5.0
<b>Panel Thickness Min(Imperial)</b>	0.13
<b>Panel Thickness Max(Imperial)</b>	0.13
<b>Panel Thickness Min (Metric)</b>	3.40

<b>Panel Thickness Max (Metric)</b>	3.3
<b>Mounting Hole Diameter D (Imperial)</b>	0.25
<b>Mounting Hole Diameter D (Metric)</b>	6.35 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	6.35
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)