

## Specification Sheet

Part Number: TM1SF10C2



Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 151-40119  |
| <b>Type</b>                    | TM1SF  |
| <b>Color</b>                   | White (WH)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Push Mounts, when used with standard cable ties, provide a permanent bundling solution.</li><li>• The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.</li></ul> |
| <b>Quantity Per</b>            | pcs.   |
| <b>Product Description</b>     | HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.                         |
| <b>Short Description</b>       | Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg  |

**Global Part Name**

TM1SF-PA66-WH

**Length L (Imperial)**

0.62

**Length L (Metric)**

15.75

**Fixation Method**

with Arrowhead / Push Mount (Mounts)

**Width W (Imperial)**

0.4

**Width W (Metric)**

10.2

**Cable Ties**

T18 - T50

**Height H (Imperial)**

.18

**Height H (Metric)**

4.60

**Cable Tie Width Max (Imperial)**

0.2

**Cable Tie Width Max (Metric)**

5.0

**Panel Thickness Min(Imperial)**

0.13

**Panel Thickness Max(Imperial)**

0.13

**Panel Thickness Min (Metric)**

3.30

**Panel Thickness Max (Metric)**

3.40

**Mounting Hole Diameter D (Imperial)**

0.25

**Mounting Hole Diameter D (Metric)**

6.35 mm

**Mounting Hole Diameter D Max (Imperial)**

0.28

**Mounting Hole Diameter D Max (Metric)**

6.35

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Certification/Specification WEB**

RST LAB | DIN EN [45545-2] (08/2013)

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

100

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

