

## Specification Sheet

Part Number: FC1.2AK2



Flat Ribbon Cable Clamp, Adhesive, 1.2" Max Cable Width, 0.156" Hole Dia, PA66, Gray, 50/pkg

<b>Article Number</b>	154-00013
<b>Type</b>	FC1.2A
<b>Color</b>	Gray (GY)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Adjustable height feature allows the clamp to close to the exact height of the ribbon cable.</li><li>•Releasable for easy access to cables when necessary.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's flat ribbon clamps route, protect, and secure flat ribbon cables without damage to sensitive wires and cables. The unique, adjustable height feature allows the clamp to close to the exact height of the ribbon cable, using only as much force as needed to secure the cable. The releasable feature allows simple opening when access to the cable is necessary.
<b>Short Description</b>	Flat Ribbon Cable Clamp, Adhesive, 1.2" Max Cable Width, 0.156" Hole Dia, PA66, Gray, 50/pkg

**Global Part Name**

FC1.2A-PA66-GY

**Length L (Imperial)**

0.75

**Length L (Metric)**

19.0

**Width W (Imperial)**

1.5

**Width W (Metric)**

38.1

**Height H (Imperial)**

0.5

**Height H (Metric)**

12.7

**Mounting Hole Diameter D (Imperial)**

0.157

**Mounting Hole Diameter D (Metric)**

4.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.157

**Mounting Hole Diameter D Max (Imperial)**

0.157

**Mounting Hole Diameter D Max (Metric)**

4.0

**Material**

Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Adhesive**

Acrylate with base of polyurethane foam

**Flammability**

UL 94 V2 (excluding adhesive)

**Adhesive Operating Temperature**

to +230°F (+110°C)

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

50

**Package Quantity (Metric)**

50

**Customs Number**

3926909988