

## Specification Sheet

Part Number: MSMP5/69C2



Cable Tie Mounting Plate, 8.08" x .62", .15" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg

<b>Article Number</b>	154-00018
<b>Type</b>	MSMP5/6
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Mounting plates allow multiple bundles to run parallel.</li><li>• The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton mounting plates allow multiple cable to be run in parallel. The mount is secured with two screws and the cables are attached to the plate by using a cable tie through any of the available slots.
<b>Short Description</b>	Cable Tie Mounting Plate, 8.08" x .62", .15" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg

Global Part Name

MSMP5/6-PA66-NA

Length L (Imperial)

8.08

Length L (Metric)

205.23

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.62

Width W (Metric)

15.8

Cable Ties

T18 - T120

Height H (Imperial)

.21

Height H (Metric)

5.30

Cable Tie Width Max (Imperial)

0.3

Cable Tie Width Max (Metric)

7.6

Mounting Hole Diameter D (Imperial)

0.15

Mounting Hole Diameter D (Metric)

3.8 mm

Mounting Hole Diameter D Max (Metric)

3.8

Mounting Hole Centers (Imperial)

1.5

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988