



## Specification Sheet

Part Number: MSMP5/69C2



Cable Tie Mounting Plate, 8.08" x .62", .15" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg

**Article Number** 154-00018

**Type** MSMP5/6

**Color** Natural (NA)

**Features & Benefits**

- Mounting plates allow multiple bundles to run parallel.
- The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.

**Quantity Per** bag

**Product Description** HellermannTyton mounting plates allow multiple cable to be run in parallel. The mount is secured with two screws and the cables are attached to the plate by using a cable tie through any of the available slots.

<b>Short Description</b>	Cable Tie Mounting Plate, 8.08" x .62", .15" Hole Dia, .3" Max Tie Width, PA66, Natural, 100/pkg
<b>Global Part Name</b>	MSMP5/6-PA66-NA
<b>Length L (Imperial)</b>	8.08
<b>Length L (Metric)</b>	205.23
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.62
<b>Width W (Metric)</b>	15.8
<b>Cable Ties</b>	T18 - T120
<b>Height H (Imperial)</b>	.21
<b>Height H (Metric)</b>	5.30
<b>Cable Tie Width Max (Imperial)</b>	0.3
<b>Cable Tie Width Max (Metric)</b>	7.6
<b>Mounting Hole Diameter D (Imperial)</b>	0.15
<b>Mounting Hole Diameter D (Metric)</b>	3.8 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	3.8

<b>Mounting Hole Centers (Imperial)</b>	1.5
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988