

Specification Sheet

Part Number: 155-03800



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.7 - 6.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

Article Number 155-03800

Type FT6LG-AMP

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Fir Tree, 0.7 - 6.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

Global Part Name

FT6LG-AMP-PA66HIRHS-BK

Fixation Method

Fir Tree

Height H (Metric)

20.5

Panel Thickness Min (Imperial)

0.028

Panel Thickness Max (Imperial)

0.24

Panel Thickness Min (Metric)

0.7

Panel Thickness Max (Metric)

6.0

Mounting Hole Diameter D (Imperial)

0.26 - 0.28

Mounting Hole Diameter D (Metric)

6.5 - 7.0 mm

Mounting Hole Diameter D Min (Imperial)

0.26

Mounting Hole Diameter D Max (Imperial)

0.28

Mounting Hole Diameter D Max (Metric)

7.0

Disc Diameter (Metric)

16.0

Disc Diameter (Imperial)

0.63

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)