

## Specification Sheet

Part Number: 155-05400



1-Pc Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

<b>Article Number</b>	155-05400
<b>Type</b>	T50SOSSB5HEC
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Oval mount design pushes on easy by hand without the need for tools.</li><li>• Design provides low insertion and high extraction force.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables
<b>Short Description</b>	1-Pc Cable Tie/Oval Stud Mount, Designed for 5.0 mm stud, 6.0" Long, PA66HS, Black, 500/pkg

**Global Part Name** T50SOSSB5HEC-PA66HS-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 170

**Length L (Imperial)** 6.0

**Length L (Metric)** 160

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

**Width W (Imperial)** 0.19

**Width W (Metric)** 4.6

**Bundle Diameter Min (Imperial)** 0.04

**Bundle Diameter Min (Metric)** 1.0

**Bundle Diameter Max (Imperial)** 1.4

**Bundle Diameter Max (Metric)** 35.0

<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.35
<b>Stud Length Max (Imperial)</b>	0.63
<b>Stud Length Max (Metric)</b>	16.0
<b>Stud Length Min (Metric)</b>	11.0
<b>Stud Diameter (Metric)</b>	5.0 mm
<b>Stud Diameter (Imperial)</b>	0.2
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500

<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	2.75