

Specification Sheet

Part Number: 155-05800



1-Pc Cable Tie/Fir Tree Mount with Disc, 6.0"L, .26"-.28" Mounting Hole, PA66HIRHS, Black, 1500/pkg

Article Number 155-05800

Type T50SOSFT6E

Color Black (BK)

Features & Benefits

- All-in-one bundling and fastening solution reduces costs and assembly time.
- Disc feature provides anti-rattle protection in high-vibration applications.

Quantity Per bag

| | |
|--|--|
| Product Description | One-piece mounting ties offer a complete solution by both bundling and mounting wires, cables and tubes. The fir tree mount provides low insertion force with a high extraction force. Outside serrations on the cable tie leave a smooth interior surface that's gentler on sensitive wire insulation. The unique head design allows the cable tie to firmly hold bundles as small as .06" diameter. The disc offers added protection against debris. |
| Short Description | 1-Pc Cable Tie/Fir Tree Mount with Disc, 6.0"L, .26"-.28" Mounting Hole, PA66HIRHS, Black, 1500/pkg |
| Global Part Name | T50SOSFT6E-PA66HIRHS-BK |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 150 |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 160 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.19 |

| | |
|--|--------------|
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.04 |
| Bundle Diameter Min (Metric) | 1.6 |
| Bundle Diameter Max (Imperial) | 1.4 |
| Bundle Diameter Max (Metric) | 32.0 |
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.35 |
| Height H (Imperial) | 0.33 |
| Panel Thickness Min(Imperial) | 0.03 |
| Panel Thickness Max(Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 0.75 |
| Panel Thickness Max (Metric) | 3.0 |
| Mounting Hole Diameter D (Imperial) | 0.26 - 0.28 |
| Mounting Hole Diameter D (Metric) | 6.5 - 7.0 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.26 |
| Mounting Hole Diameter D Max (Imperial) | 0.28 |
| Mounting Hole Diameter D Max (Metric) | 7.0 |

| | |
|---------------------------------------|--|
| Disc Diameter(Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 1500 |
| Package Quantity (Metric) | 1500 |
| Customs Number | 3926909988 |
| Content Unit(BMEcat) | pcs. |
| Weight (Metric) | 2.0 |

