

## Specification Sheet

Part Number: 155-11601



The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.

Bundling Clip with Arrowhead, 2.17" Long, 0.06" - 0.12" Panel Thickness, PA66HIRHS, Black, 500/pkg

**Article Number** 155-11601

**Type** BCSFT6.5 16-3MD

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.

**Short Description** Bundling Clip with Arrowhead, 2.17" Long, 0.06" - 0.12" Panel Thickness, PA66HIRHS, Black, 500/pkg

**Global Part Name** BCSFT6.5 16-3MD-PA66HIRHS-BK

<b>Length L (Imperial)</b>	2.17
<b>Length L (Metric)</b>	55.0
<b>Fixation Method</b>	Arrowhead
<b>Width W (Imperial)</b>	0.32
<b>Width W (Metric)</b>	8.0
<b>Height H (Imperial)</b>	0.55
<b>Height H (Metric)</b>	14.0
<b>Panel Thickness Min (Imperial)</b>	0.06
<b>Panel Thickness Max (Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	1.5
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.25 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.3 - 6.7 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.25
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Metric)</b>	6.7

<b>Disc Diameter (Metric)</b>	16.0
<b>Disc Diameter (Imperial)</b>	0.63
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988