

## Specification Sheet

Part Number: 155-17801



Convoluted Tubing Clip, 0.4" Max Bundle Diameter, .02"-.12" Panel Thick, PA66HIRHS, Black, 500/pkg

**Article Number**

155-17801

**Type**

CTC10FT9

**Color**

Black (BK)

**Features & Benefits**

- Clip includes an internal rib that spans the inside of the bracket to fit securely into the profile of the tubing to prevent lateral movement and slipping of the tubing.
- Extended fir tree allows for a wide range of panel thicknesses.
- Fir tree design provides low insertion forces and high extraction forces.

**Quantity Per**

bag

**Product Description**

Convoluted Tube Clips provide a quick and easy method for firmly securing corrugated covered cables and wires to a surface. Applications such as this can be found in a wide variety of industries such as the wire harness, automotive, trucking, and heavy equipment manufacturing industries.

<b>Short Description</b>	Convuluted Tubing Clip, 0.4" Max Bundle Diameter, .02"-.12" Panel Thick, PA66HIRHS, Black, 500/pkg
<b>Global Part Name</b>	CTC10FT9-PA66HIRHS-BK
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.31
<b>Width W (Metric)</b>	8.0
<b>Height H (Imperial)</b>	0.89
<b>Height H (Metric)</b>	22.7
<b>Nominal Diameter (Imperial)</b>	3/8
<b>Nominal Diameter (Metric)</b>	10.0
<b>Panel Thickness Min(Imperial)</b>	0.12
<b>Panel Thickness Max(Imperial)</b>	0.20
<b>Panel Thickness Min (Metric)</b>	3.0
<b>Panel Thickness Max (Metric)</b>	5.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.34 -0.35
<b>Mounting Hole Diameter D (Metric)</b>	8.7 - 9.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.34

<b>Mounting Hole Diameter D Max (Imperial)</b>	0.35
--	------

<b>Mounting Hole Diameter D Max (Metric)</b>	9.0
--	-----

<b>Disc Diameter(Metric)</b>	23.0
------------------------------	------

<b>Disc Diameter (Imperial)</b>	0.87
---------------------------------	------

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
-----------------	--

<b>Material Shortcut</b>	PA66HIRHS
--------------------------	-----------

<b>Flammability</b>	UL 94 HB
---------------------	----------

<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
---------------------------------------	-----------------------------------

<b>Reach Complaint(Article 33)</b>	Yes
------------------------------------	-----

<b>ROHS Complaint</b>	Yes
-----------------------	-----

<b>Package Quantity(Imperial)</b>	500
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	500
----------------------------------	-----

<b>Customs Number</b>	3926909987
-----------------------	------------

<b>Content Unit(BMEcat)</b>	pcs.
-----------------------------	------

<b>Weight (Metric)</b>	1.4
------------------------	-----

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)