

## Specification Sheet

Part Number: 155-30602



Design gives quick and easy assembly by hand without the need for tools.

Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts.

Design provides low insertion force and high extraction force.

<b>Article Number</b>	155-30602
<b>Type</b>	T50SSBS5OT-E
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.
<b>Short Description</b>	Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg
<b>Global Part Name</b>	T50SSBS5OT-E-PA66HS-BK

<b>Minimum Tensile Strength (Imperial)</b>	45.0
<b>Minimum Tensile Strength (Metric)</b>	200
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	160
<b>Fixation Method</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.16
<b>Bundle Diameter Min (Metric)</b>	4.0
<b>Bundle Diameter Max (Imperial)</b>	1.4
<b>Bundle Diameter Max (Metric)</b>	35.0
<b>Thickness T (Imperial)</b>	0.05

<b>Thickness T (Metric)</b>	1.35
<b>Stud Length Max (Imperial)</b>	0.65
<b>Stud Length Max (Metric)</b>	16.5
<b>Stud Diameter (Metric)</b>	5.0 mm
<b>Stud Diameter (Imperial)</b>	0.2
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL 94 V-2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)