

## Specification Sheet

Part Number: 155-30802



Bundling Clip with Fir Tree, 2.17" Long, 0.02 - 0.20" Panel Thickness, PA66HIRHS,Bk,14,000/pkg

<b>Article Number</b>	155-30802
<b>Type</b>	TC2FT6LG
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton Bundling Clips are designed to provide simple and easy methods for securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using tape or cable ties.
<b>Short Description</b>	Bundling Clip with Fir Tree, 2.17" Long, 0.02 - 0.20" Panel Thickness, PA66HIRHS,Bk,14,000/pkg

Global Part Name

TC2FT6LG-PA66HIRHS-BK

Length L (Imperial)

2.17

Length L (Metric)

55.0

Fixation Method

Fir Tree

Width W (Imperial)

0.355

Width W (Metric)

9.0

Height H (Imperial)

0.49

Height H (Metric)

12.5

Panel Thickness Min(Imperial)

0.02

Panel Thickness Max(Imperial)

0.20

Panel Thickness Min (Metric)

0.6

Panel Thickness Max (Metric)

5.1

Mounting Hole Diameter D (Imperial)

0.25 - 0.28

Mounting Hole Diameter D (Metric)

6.3 - 7.0 mm

Mounting Hole Diameter D Min (Imperial)

0.25

Mounting Hole Diameter D Max (Imperial)

0.28

Mounting Hole Diameter D Max (Metric)

7.0

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	14000
<b>Package Quantity (Metric)</b>	14000
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	1.0