

Specification Sheet

Part Number: 155-32602



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

Article Number 155-32602

Type FT6LG.M.St.Aufn.II

Color Black (BK)

Quantity Per bag

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Fir Tree, 0.75 - 5.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

Global Part Name

FT6LG.M.St.Aufn.II-PA66HIRHS-BK

Length L (Imperial)

1.06

Length L (Metric)

27

Fixation Method

Fir Tree

Variant

6.5 - 7.0 mm

Width W (Imperial)

0.63

Width W (Metric)

16

Height H (Imperial)

0.68

Height H (Metric)

17.3

Panel Thickness Min (Imperial)

0.03

Panel Thickness Max (Imperial)

0.2

Panel Thickness Min (Metric)

0.75

Panel Thickness Max (Metric)

1.5

Mounting Hole Diameter D (Imperial)

0.26 - 0.28

Mounting Hole Diameter D (Metric)

6.5 - 7.0 mm

Mounting Hole Diameter D Min (Imperial)

0.26

Mounting Hole Diameter D Max (Imperial) 0.28

Mounting Hole Diameter D Max (Metric) 7.0

Disc Diameter (Metric) 16

Disc Diameter (Imperial) 0.63

Material Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

