

## Specification Sheet

Part Number: 155-36002



Head design contains clamping rails to provide full circumferential compression around bundles. Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.6 - 3.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 1000/pkg

**Article Number** 155-36002

**Type** STECKERHALTER SITZ

**Color** Black (BK)

**Quantity Per** pcs.

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Fir Tree, 0.6 - 3.0 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 1000/pkg

**Global Part Name**

STECKERHALTER SITZ-PA66HIRHS-BK

<b>Length L (Imperial)</b>	1.32
<b>Length L (Metric)</b>	33.5
<b>Fixation Method</b>	Fir Tree
<b>Width W (Imperial)</b>	0.4
<b>Width W (Metric)</b>	10.3
<b>Height H (Imperial)</b>	0.6
<b>Height H (Metric)</b>	15.2
<b>Panel Thickness Min (Imperial)</b>	0.02
<b>Panel Thickness Max (Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.26 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.5 - 7.0 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.26
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28

**Mounting Hole Diameter D Max (Metric)** 7.0

**Material** Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut** PA66HIRHS

**Flammability** UL 94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 1000

**Package Quantity (Metric)** 1000

**Customs Number** 3926909988