

## Specification Sheet

Part Number: 155-38102



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Conn. Clip w/Fir Tree, 0.75 - 1.5 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

**Article Number** 155-38102

**Type** YCC-FT6-S

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

**Short Description** Conn. Clip w/Fir Tree, 0.75 - 1.5 mm Panel Thick., 6.5 - 7.0 mm Hole Dia., PA66HIRHS, Black, 500/pkg

**Global Part Name**

YCC-FT6-S-PA66HIRHS-BK

**Fixation Method**

Fir Tree

**Height H (Imperial)**

0.48

**Height H (Metric)**

12.1

**Panel Thickness Min (Imperial)**

0.04

**Panel Thickness Max (Imperial)**

0.06

**Panel Thickness Min (Metric)**

0.75

**Panel Thickness Max (Metric)**

1.5

**Mounting Hole Diameter D (Imperial)**

0.26 - 0.28

**Mounting Hole Diameter D (Metric)**

6.5 - 7.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.26

**Mounting Hole Diameter D Max (Imperial)**

0.275

**Mounting Hole Diameter D Max (Metric)**

7.0

**Disc Diameter (Metric)**

16

**Disc Diameter (Imperial)**

0.63

<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)