

## Specification Sheet

Part Number: 155-43802

HellermannTyton connector clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. Detailed designs include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges.



HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Conn. Clip w/Oval Arrowhead, 1.2-2.0mm Panel Thick, 7.0x12.0mm Hole Dia., PA66HIRHS, Black, 1000/pkg

Article Number	155-43802
Type	CCAMPSFT7.0x12.0
Color	Black (BK)
Quantity Per	bag
Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description	Conn. Clip w/Oval Arrowhead, 1.2-2.0mm Panel Thick, 7.0x12.0mm Hole Dia., PA66HIRHS, Black, 1000/pkg
Global Part Name	CCAMPSFT7.0x12.0-PA66HIRHS-BK
Length L (Imperial)	0.63
Length L (Metric)	16.0
Fixation Method	Arrowhead for oval holes
Width W (Metric)	16.0
Height H (Imperial)	0.69
Height H (Metric)	17.6
Panel Thickness Max (Imperial)	0.08
Panel Thickness Min (Metric)	1.2
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.28 - 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm
Mounting Hole Diameter D Min (Imperial)	0.28
Mounting Hole Diameter D Max (Imperial)	0.472

Mounting Hole Diameter D Max (Metric)	12.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988