

Specification Sheet

Part Number: 156-00067



Heavy Duty Cable Tie/Fir Tree Mount, 15" x .3", .04"-.25" Panel Thick, PA66HS/PA66HIRHSUV, Black, 100/pkg

Article Number

156-00067

Type

T120RFT9A

Color

Black (BK)

Features & Benefits

- Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.
- Fir tree provides low insertion effort yet demonstrates high extraction resistance.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

Quantity Per

bag

Product Description

HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description

Heavy Duty Cable Tie/Fir Tree Mount, 15" x .3", .04"-.25" Panel Thick, PA66HS/PA66HIRHSUV, Black, 100/pkg

Global Part Name

T120RFT9A-PA66HS/PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

15.0

Length L (Metric)

380.0

Fixation Method

Fir Tree

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.3

Width W (Metric)

7.6

Bundle Diameter Max (Imperial)

4.0

Bundle Diameter Max (Metric)

100.0

Height H (Imperial)

.07

Height H (Metric)

1.80

Panel Thickness Min(Imperial)	0.039
Panel Thickness Max(Imperial)	0.256
Panel Thickness Min (Metric)	1.0
Panel Thickness Max (Metric)	6.5
Mounting Hole Diameter D (Imperial)	0.34 - 0.36
Mounting Hole Diameter D (Metric)	8.7 - 9.2 mm
Mounting Hole Diameter D Min (Imperial)	0.34
Mounting Hole Diameter D Max (Imperial)	0.36
Mounting Hole Diameter D Max (Metric)	9.2
Disc Diameter(Metric)	21.6
Disc Diameter (Imperial)	0.85
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV PA66HS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB

Operating Temperature (Metric)

-40°F to +257°F (-40°C to +125°C) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909988

Content Unit(BMEcat)

pcs.