

Specification Sheet

Part Number: 156-00264



Arrowhead design makes installation quick and easy by hand.

Ties "clicks" into place upon final installation signaling installer insertion is complete.

Design provides low insertion and high extraction force.

1-Pc Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 4000/bag

| | |
|----------------------------|--|
| Article Number | 156-00264 |
| Type | T50SOSSFT6.5E-MDL |
| Color | Black (BK) |
| Quantity Per | bag |
| Product Description | Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times. |
| Short Description | 1-Pc Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 4000/bag |
| Global Part Name | T50SOSSFT6.5E-MDL-PA66HS-BK |

| | |
|--|------------------|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 6.3 |
| Length L (Metric) | 158.8 |
| Fixation Method | Arrowhead |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 1.2 |
| Bundle Diameter Max (Metric) | 30.0 |
| Thickness T (Imperial) | 0.05 |

| | |
|--|--------------|
| Thickness T (Metric) | 1.3 |
| Height H (Imperial) | 0.67 |
| Panel Thickness Min (Imperial) | 0.02 |
| Panel Thickness Max (Imperial) | 0.07 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 1.8 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.26 |
| Mounting Hole Diameter D (Metric) | 6.3 - 6.7 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.26 |
| Mounting Hole Diameter D Max (Metric) | 6.7 |
| Disc Diameter (Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

| | |
|-------------------------------------|-----------------------------------|
| Flammability | UL 94 V2 |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 3500 |
| Package Quantity (Metric) | 3500 |
| Customs Number | 3926909988 |

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)