

Specification Sheet

Part Number: 156-00264



1-Piece Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag

| | |
|--------------------------------|--|
| Article Number | 156-00264 |
| Type | T50SOSSFT6.5E-MDL |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">• Arrowhead design makes installation quick and easy by hand.• Ties "clicks" into place upon final installation signaling installer insertion is complete.• Design provides low insertion and high extraction force. |
| Quantity Per | bag |
| Product Description | Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times. |
| Short Description | 1-Piece Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag |

Global Part Name

T50SOSSFT6.5E-MDL-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

6.3

Length L (Metric)

158.8

Fixation Method

Arrowhead

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.2

Bundle Diameter Max (Metric)

30.0

Thickness T (Imperial)

0.05

| | |
|--|--|
| Thickness T (Metric) | 1.3 |
| Height H (Imperial) | 0.67 |
| Panel Thickness Min(Imperial) | 0.02 |
| Panel Thickness Max(Imperial) | 0.07 |
| Panel Thickness Min (Metric) | 0.6 |
| Panel Thickness Max (Metric) | 1.8 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.26 |
| Mounting Hole Diameter D (Metric) | 6.3 - 6.7 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.26 |
| Mounting Hole Diameter D Max (Metric) | 6.7 |
| Disc Diameter(Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V2 |

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 4000

Package Quantity (Metric) 4000

Customs Number 3926909988

Content Unit(BMEcat) pcs.

Weight (Metric) 1.51