

Specification Sheet

Part Number: 156-00291



2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .26"-.28" Mounting Hole, 30lb, PA66HS, Black, 100/pkg

Article Number

156-00291

Type

T50RFT7

Color

Black (BK)

Features & Benefits

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

Quantity Per

bag

Product Description

HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description

2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .26"-.28" Mounting Hole, 30lb, PA66HS, Black, 100/pkg

Global Part Name

T50RFT7-PA66HS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.0

Length L (Metric)

203.2

Fixation Method

Fir Tree

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.8

Bundle Diameter Max (Metric)	45.0
Height H (Imperial)	.05
Height H (Metric)	1.20
Panel Thickness Min(Imperial)	0.03
Panel Thickness Max(Imperial)	0.28
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	7.0
Mounting Hole Diameter D (Imperial)	0.26 - 0.28
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
Mounting Hole Diameter D Max (Imperial)	0.8
Mounting Hole Diameter D Max (Metric)	7.0
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
Material Shortcut	PA66HS
Flammability	UL 94 V2

Operating Temperature (Metric)

-40°F to +221°F (-40°C to +105°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987