

Specification Sheet

Part Number: 156-00456



2-Piece Cable Tie/Arrowhead Mount, 7.9" Long, 50lb Tensile, .25"-.26" Hole, .07"-.09" Pnl, PA46/PEEK, Gray/Bge, 100/pkg

Article Number	156-00456
Type	T50ROSP2SFT6.5
Color	Beige (BGE) Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• The arrowhead design of this push mount offers a low insertion force and a high extraction force.• Integrated cap keeps out debris.
Quantity Per	bag
Product Description	The Arrowhead Mount Tie is a two-piece bundling and fastening solution that delivers strong extraction force. The disc blocks debris ingress through the mounting hole. This convenient combination is used in many markets, including automobile, aircraft and appliance.
Short Description	2-Piece Cable Tie/Arrowhead Mount, 7.9" Long, 50lb Tensile, .25"-.26" Hole, .07"-.09" Pnl, PA46/PEEK, Gray/Bge, 100/pkg

Global Part Name

T50ROSP2SFT6.5-PA46/PEEK-GY/BGE

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

7.9

Length L (Metric)

200.0

Fixation Method

Arrowhead

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.04

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

1.8

Bundle Diameter Max (Metric)

45.0

Thickness T (Imperial)

0.05

Thickness T (Metric)

1.3

Height H (Imperial)	0.63
Height H (Metric)	16.0
Panel Thickness Min(Imperial)	0.07
Panel Thickness Max(Imperial)	0.09
Panel Thickness Min (Metric)	1.7
Panel Thickness Max (Metric)	2.3
Mounting Hole Diameter D (Imperial)	0.25 - 0.26
Mounting Hole Diameter D (Metric)	6.3 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7
Disc Diameter(Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyetheretherketone (PEEK) Polyamide 4.6 (PA46)
Material Shortcut	PEEK PA46
Material Cable Tie	Polyamide 4.6 (PA46)

Flammability

UL 94 V0 UL 94 V2

Operating Temperature (Metric)

-67°F to +464°F (-55°C to +240°C) -40°F to +302°F (-40°C to +150°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909988

Content Unit(BMEcat)

pcs.

Weight (Metric)

1.4