

## Specification Sheet

Part Number: 156-00555



2-Piece Cable Tie & Edge Clip, 8.0" Long, EC20, 3-6 mm Panel, 50lb, PA66HS/PA66HIRHSUV, Black, 500/pkg

**Article Number**

156-00555

**Type**

T50REC20

**Color**

Black (BK)

**Features & Benefits**

- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
- Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

**Quantity Per**

bag

**Product Description**

HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

**Short Description**

2-Piece Cable Tie &amp; Edge Clip, 8.0" Long, EC20, 3-6 mm Panel, 50lb, PA66HS/PA66HIRHSUV, Black, 500/pkg

**Global Part Name**

T50REC20-PA66HS/PA66HIRHS-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

8.0

**Length L (Metric)**

202.0

**Fixation Method**

EdgeClip, top, assembled, 2 piece

**Identification Plate Position**

none

**Variant**

Inside Serrated

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.20

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

2.0

**Bundle Diameter Max (Metric)**

50.0

**Thickness T (Imperial)**

0.05

|                                       |   |
|---------------------------------------|---|
| <b>Thickness T (Metric)</b>           | 1.2   |
| <b>Height H (Imperial)</b>            | 0.05  |
| <b>Height H (Metric)</b>              | 1.2   |
| <b>Panel Thickness Min(Imperial)</b>  | 0.12  |
| <b>Panel Thickness Max(Imperial)</b>  | 0.24  |
| <b>Panel Thickness Min (Metric)</b>   | 3.0   |
| <b>Panel Thickness Max (Metric)</b>   | 6.0   |
| <b>Material</b>                       | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| <b>Material Shortcut</b>              | PA66HIRHS PA66HS  |
| <b>Material Cable Tie</b>             | Polyamide 6.6 heat stabilized (PA66HS)  |
| <b>Flammability</b>                   | UL 94 HB  |
| <b>Operating Temperature (Metric)</b> | -40°F to +230°F (-40°C to +110°C) -40°F to +221°F (-40°C to +105°C)                                     |
| <b>ROHS Complaint</b>                 | Yes   |
| <b>Package Quantity(Imperial)</b>     | 500   |
| <b>Package Quantity (Metric)</b>      | 500   |

**Customs Number**

3926909987

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)