

## Specification Sheet

Part Number: 156-00567



2-Piece Cable Tie & Edge Clip, 8.0" Long, EC23, 3-6 mm Panel, 45lb, PP/PA66HIRHSUV, Black, 500/pkg

**Article Number** 156-00567

**Type** T50REC23

**Color** Black (BK)

**Features & Benefits**

- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
- Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

**Quantity Per** bag

**Product Description**

HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

<b>Short Description</b>	2-Piece Cable Tie & Edge Clip, 8.0" Long, EC23, 3-6 mm Panel, 45lb, PP/PA66HIRHSUV, Black, 500/pkg
<b>Global Part Name</b>	T50REC23-PP/PA66HIRHS-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Fixation Method</b>	EdgeClip, sideways, assembled, 2 piece
<b>Identification Plate Position</b>	none
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.20
<b>Bundle Diameter Min (Metric)</b>	5.0
<b>Bundle Diameter Max (Imperial)</b>	2.0
<b>Bundle Diameter Max (Metric)</b>	50.0

<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.2
<b>Height H (Imperial)</b>	0.05
<b>Height H (Metric)</b>	1.2
<b>Panel Thickness Min (Imperial)</b>	0.12
<b>Panel Thickness Max (Imperial)</b>	0.24
<b>Panel Thickness Min (Metric)</b>	3.0
<b>Panel Thickness Max (Metric)</b>	6.0
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polypropylene (PP)
<b>Material Shortcut</b>	PA66HIRHS PP
<b>Material Cable Tie</b>	Polypropylene (PP)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C) -40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes

**Package Quantity (Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988