

## Specification Sheet

Part Number: 156-00591



Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

2-Piece Cable Tie & Edge Clip, 8.0" Long, EC20, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Article Number 156-00591

Type T50REC20

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

Short Description 2-Piece Cable Tie & Edge Clip, 8.0" Long, EC20, 3-6 mm Panel, 50lb, PA66UV/PA66HIRHSUV, Black, 100/pkg

Global Part Name T50REC20-PA66UV/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 8.0

Length L (Metric) 202.0

Fixation Method EdgeClip, top, assembled, 2 piece

Identification Plate Position none

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.20

Bundle Diameter Min (Metric) 5.0

Bundle Diameter Max (Imperial) 2.0

Bundle Diameter Max (Metric) 50.0

Thickness T (Imperial) 0.05

Thickness T (Metric) 1.2

|                                |   |
|--------------------------------|---|
| Height H (Imperial)            | 0.05  |
| Height H (Metric)              | 1.2   |
| Panel Thickness Min (Imperial) | 0.12  |
| Panel Thickness Max (Imperial) | 0.24  |
| Panel Thickness Min (Metric)   | 3.0   |
| Panel Thickness Max (Metric)   | 6.0   |
| Material                       | Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut              | PA66UV PA66HIRHS  |
| Material Cable Tie             | Polyamide 6.6 UV-stabilized (PA66UV)  |
| Flammability                   | UL 94 HB  |
| Operating Temperature          | -40°F to +185°F (-40°C to +85°C) -40°F to +230°F (-40°C to +110°C)                                    |
| ROHS Compliant                 | Yes   |
| Package Quantity (Imperial)    | 100   |
| Package Quantity (Metric)      | 100   |

Customs Number

3926909988

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)