

## Specification Sheet

Part Number: 156-00594



Bundle can rotate to any orientation, allowing routing in any direction regardless of mounting point. Clip is reusable, making relocation or adjustments simple. All-in-one bundling and mounting solution reduces costs.

2-Piece Cable Tie with Pipe Clip, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pkg

**Article Number** 156-00594

**Type** T50ROC2

**Color** Black (BK)

**Quantity Per** bag

**Product Description** HellermannTyton's 2-Piece Cable Tie with Pipe Clip secures cables to tubular frame rails. The cable tie bundles wires, cables or tubes, and the C-clip snaps onto the tubular frame rail. The clip can be removed from the mounting surface and reinstalled without additional fasteners.

**Short Description** 2-Piece Cable Tie with Pipe Clip, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pkg

<b>Global Part Name</b>	T50ROC2-PA66HSUV/PA66HIRHS-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Fixation Method</b>	Omega Clips
<b>Identification Plate Position</b>	none
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.26
<b>Bundle Diameter Min (Metric)</b>	6.5
<b>Bundle Diameter Max (Imperial)</b>	1.8
<b>Bundle Diameter Max (Metric)</b>	45.0
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat and UV stabilized (PA66HSUV)

<b>Material Shortcut</b>	PA66HIRHS PA66HSUV
<b>Material Cable Tie</b>	Polyamide 6.6 UV-stabilized (PA66UV)
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)