

## Specification Sheet

Part Number: 156-00911



2-Piece Cable Tie/Oval Stud Mount, 11.8" Long, 50lb Tensile Strength, PA66HIRHS, Black, 250/pkg

**Article Number**

156-00911

**Type**

T50ISBS520-40

**Color**

Black (BK)

**Features & Benefits**

- Head allows for a .2" lateral adjustment on stud during installation.
- Quick and easy installation ideal for manufacturing environment.

**Quantity Per**

bag

**Product Description**

Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.

**Short Description**

2-Piece Cable Tie/Oval Stud Mount, 11.8" Long, 50lb Tensile Strength, PA66HIRHS, Black, 250/pkg

Global Part Name

T50ISBS520-40-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

11.8

Length L (Metric)

300.0

Fixation Method

Weld Stud Fixing

Identification Plate Position

none

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.79

Bundle Diameter Min (Metric)

20.0

Bundle Diameter Max (Imperial)

1.57

Bundle Diameter Max (Metric)

40.0

Stud Length Min (Imperial)

0.56

Stud Length Min (Metric)

14.2

<b>Stud Diameter (Metric)</b>	5.0 mm
<b>Stud Diameter (Imperial)</b>	0.20
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3926909988