

Specification Sheet

Part Number: 156-01096

High tensile strength delivers reliable performance for heavy duty applications.

Low-profile design allows for mount to be placed in areas where space is limited.

A suitable alternative for metal clamps.

Robust design withstands vibration and displacement forces.

Metal bushing provides high tightening torque.



2-Piece Cable Tie/Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS/PA66UV, Black, 200/pkg

Article Number	156-01096
Type	X120RDHDM6
Color	Black (BK)
Quantity Per	carton
Product Description	Multi-piece heavy duty dual clamp ties provide parallel separation between high-voltage cables to protect them from abrasion. A variety of mounting hole options are available for securing bundles along the chassis or body of today's electric vehicles.
Short Description	2-Piece Cable Tie/Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS/PA66UV, Black, 200/pkg

Global Part Name X120RDHDM6-PA66HIRHS/PA66UV-BK

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 14.53

Length L (Metric) 369.0

Fixation Method Screw Mounting and Rivet

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.30

Width W (Metric) 7.7

Bundle Diameter Min (Imperial) 0.40

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 3.94

Bundle Diameter Max (Metric) 100.0

Thickness T (Metric) 1.6

Height H (Imperial) 0.61

Height H (Metric)	15.5
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	6.2 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66HIRHS PA66UV
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	200
Package Quantity (Metric)	200

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin.

