

## Specification Sheet

Part Number: 156-01096

High tensile strength delivers reliable performance for heavy duty applications.

Low-profile design allows for mount to be placed in areas where space is limited.



A suitable alternative for metal clamps.

Robust design withstands vibration and displacement forces.

Metal bushing provides high tightening torque.

2-Pc Cable Tie/Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS, Black, 50/pkg

Article Number	156-01096
Type	X120RDHDM6
Color	Black (BK)
Quantity Per	carton
Product Description	Multi-piece heavy duty dual clamp ties provide parallel separation between high-voltage cables to protect them from abrasion. A variety of mounting hole options are available for securing bundles along the chassis or body of today's electric vehicles.
Short Description	2-Pc Cable Tie/Screw Mount, 14.5"L, 0.24" Hole, 3.94" Max Bundle Dia, 120 lb, PA66HIRHS, Black, 50/pkg

Global Part Name X120RDHDM6-PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 120

Minimum Tensile Strength (Metric) 535

Length L (Imperial) 14.53

Length L (Metric) 369.0

Fixation Method Fixing hole

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.30

Width W (Metric) 7.7

Bundle Diameter Min (Imperial) 0.40

Bundle Diameter Min (Metric) 10.0

Bundle Diameter Max (Imperial) 3.94

Bundle Diameter Max (Metric) 100.0

Thickness T (Metric) 1.6

Height H (Imperial) 0.61

Height H (Metric)	15.5
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	6.2 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50