

Specification Sheet

Part Number: 156-01294



Head allows for a 0.2" lateral adjustment on stud during installation. Quick and easy installation ideal for manufacturing environment.

2-Piece Cable Tie/Oval Stud Mount, 8.0" Long, 50lb Tensile, With Thumb Bar, PA66HIRHS, Gray, 2000/box

| | |
|----------------------------|--|
| Article Number | 156-01294 |
| Type | T50R0GSBL5U-SET |
| Color | Black (BK) Gray (GY) |
| Quantity Per | carton |
| Product Description | Oval Shaped Stud Mount's special design allows for a 0.2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools. |
| Short Description | 2-Piece Cable Tie/Oval Stud Mount, 8.0" Long, 50lb Tensile, With Thumb Bar, PA66HIRHS, Gray, 2000/box |
| Global Part Name | T50R0GSBL5U-SET-PA66/PA66HIRHS-BK/GY |

| | |
|--|------------------|
| Minimum Tensile Strength (Imperial) | 25.0 |
| Minimum Tensile Strength (Metric) | 110 |
| Length L (Imperial) | 8.0 |
| Length L (Metric) | 203.2 |
| Fixation Method | Weld Stud Fixing |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Width W (Imperial) | 0.55 |
| Bundle Diameter Min (Imperial) | 0.16 |
| Bundle Diameter Min (Metric) | 4.0 |
| Bundle Diameter Max (Imperial) | 1.97 |
| Bundle Diameter Max (Metric) | 50.0 |
| Height H (Imperial) | 1.02 |
| Height H (Metric) | 25.0 |
| Mounting Hole Diameter D (Metric) | T5 M5 x 0.8 |

| | |
|-------------------------------------|---|
| Stud Diameter (Metric) | 5.0 mm |
| Stud Diameter (Imperial) | 0.20 |
| Material | Polyamide 6.6 (PA66) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut | PA66HIRHS PA66 |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 2000 |
| Package Quantity (Metric) | 2000 |
| Customs Number | 3926909988 |