

Specification Sheet

Part Number: 156-01429

Design gives quick and easy assembly by hand without the need for tools.

Mount can be used in a wide variety of applications where 8mm weld studs or 8mm ISO bolts.

Design provides low insertion force and high extraction force.



2-Piece M8 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHSUV, Black, 2000/pkg

| | |
|----------------|------------|
| Article Number | 156-01429 |
| Type | T50RSB8SET |
| Color | Black (BK) |
| Quantity Per | bag |

Product Description

Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description

2-Piece M8 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHSUV, Black, 2000/pkg

Global Part Name T50RSB8SET-PA66HS/PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225.0

Length L (Imperial) 7.95

Length L (Metric) 202.0

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.181

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.97

Bundle Diameter Max (Metric) 50.0

Thickness T (Metric) 1.2

| | |
|-----------------------------|---|
| Height H (Imperial) | 0.98 |
| Height H (Metric) | 25.0 |
| Stud Diameter (Metric) | 8.0 mm |
| Stud Diameter (Imperial) | 0.31 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV PA66HS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Operating Temperature | -40°F to +257°F (-40°C to +125°C) -40°F to +221°F (-40°C to +105°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 2500 |
| Package Quantity (Metric) | 2500 |
| Customs Number | 3926909988 |

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)