

Specification Sheet

Part Number: 156-01547



2-Piece M5/T5/M6/T6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 3000/pkg

Article Number	156-01547
Type	T50R0SBS5-6U-SET
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• Versatile design allows cable routing above, perpendicular or parallel to stud.• Can mount up to three bundles simultaneously, making efficient use of a single mounting point.• Four-pawl, three-tooth design delivers outstanding stud retention to keep bundles secure.• PA46 material option allows use in high-heat applications.
Quantity Per	carton

Product Description

Unique, two-piece design allows routing to be above, parallel or perpendicular to stud. This also enables up to three separate bundles to be fastened to the same stud. With their low insertion force and high extraction performance, HellermannTyton mounting ties offer the ideal combination of high-grade materials and superior design to suit the mounting and bundling needs of complex applications. Available in standard and high-heat material options.

Short Description

2-Piece M5/T5/M6/T6 Stud Mount Tie, 8.0" Tie, 50lb Tensile Strength, PA66HS/PA66HIRHS, BK, 3000/pkg

Global Part Name

T50R0SBS5-6U-SET-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

223

Length L (Imperial)

8.0

Length L (Metric)

202.0

Fixation Method

Stud Mount

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Width W (Imperial)

0.92

Width W (Metric)

23.25

Bundle Diameter Min (Imperial)

0.16

Bundle Diameter Min (Metric)

4.0

Bundle Diameter Max (Imperial)

1.97

Bundle Diameter Max (Metric)

50.0

Cable Ties	156-01547
Height H (Imperial)	0.74
Height H (Metric)	18.75
Mounting Hole Diameter D (Imperial)	0.20" x 0.03"; 0.24" x 0.04"; 0.20
Mounting Hole Diameter D (Metric)	T5 M6 x 1 M5 x 0.8
Stud Diameter (Metric)	5.0 mm 6.0 mm
Stud Diameter (Imperial)	0.20 ", 0.24
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.0039

Weight (Imperial)

0.009