

Specification Sheet

Part Number: 156-01555



2-Piece Cable Tie/Fir Tree Mount, 5.9"L, .22"-.25" Mounting Hole, 100lb, PAEK, Beige, 500/bag

Article Number	156-01555
Type	PAT100RFT6LG
Color	Beige (BGE)
Features & Benefits	<ul style="list-style-type: none">•Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.•Fir tree provides low insertion effort yet demonstrates high extraction resistance.•Disc feature prevents rattling in high-vibration applications and protects against debris ingress.
Quantity Per	bag
Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole. The mount can slide along the cable tie to adjust orientation as needed. Fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description

2-Piece Cable Tie/Fir Tree Mount, 5.9"L, .22"-.25" Mounting Hole, 100lb, PAEK, Beige, 500/bag

Global Part Name

PAT100RFT6LG-PAEK-BGE

Minimum Tensile Strength (Imperial)

100.0

Minimum Tensile Strength (Metric)

445

Length L (Imperial)

5.9

Length L (Metric)

149.9

Fixation Method

Fir Tree

Identification Plate Position

none

Tie Closure

plastic pawl

Width W (Imperial)

0.33

Width W (Metric)

8.0

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

35.0

Height H (Imperial)

.75

Height H (Metric)	19.20
Panel Thickness Min(Imperial)	0.05
Panel Thickness Max(Imperial)	0.236
Panel Thickness Min (Metric)	1.25
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.22 - 0.25
Mounting Hole Diameter D (Metric)	5.6 - 6.4 mm
Mounting Hole Diameter D Min (Imperial)	0.22
Mounting Hole Diameter D Max (Imperial)	0.25
Mounting Hole Diameter D Max (Metric)	6.4
Disc Diameter(Metric)	18.6
Disc Diameter (Imperial)	0.73
Material	Polyaryletherketone (PAEK)
Material Shortcut	PAEK
Flammability	UL 94 V0
Halogen free	No

Operating Temperature (Metric)

-67°F to +392°F (-55°C to +200°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909988