

Specification Sheet

Part Number: 156-01564



LOC Locking Clamp, 20–25 mm, Unassembled to T50R Tie, PA66HIRHSUV, Black, 1000/ctn

Article Number

156-01564

Type

T50RLOC20-25SET

Color

Black (BK)

Features & Benefits

- The 360 degree locking enclosure and cable tie dynamically fit a range of bundle sizes.
- Clamp can be opened for bundle maintenance.
- Low-profile release tab won't interfere with bundle or nearby routing.
- The two bundles are allowed to rotate up to 90 degrees from one another.

Quantity Per

carton

Product Description

The 2-Piece LOC with Saddle to T50R Tie has a two-piece design that keeps two routings secured together while providing a semi-fixed orientation for each bundle. The saddle design allows 90-degree rotation of the bundles. Tie provides additional security against axial slip by clamping around solid tube, pipe or harness.

Short Description	LOC Locking Clamp, 20–25 mm, Unassembled to T50R Tie, PA66HIRHSUV, Black, 1000/ctn
--------------------------	--

Global Part Name	T50RLOC20-25SET-PA66HIRHSUV-BK
-------------------------	--------------------------------

Minimum Tensile Strength (Imperial)	50
--	----

Minimum Tensile Strength (Metric)	225
--	-----

Length L (Imperial)	1.46
----------------------------	------

Length L (Metric)	37.2
--------------------------	------

Fixation Method	Omega Clips
------------------------	-------------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Inside Serrated
----------------	-----------------

Bundle Diameter Min (Imperial)	0.79
---------------------------------------	------

Bundle Diameter Min (Metric)	20.0
-------------------------------------	------

Bundle Diameter Max (Imperial)	0.98
---------------------------------------	------

Bundle Diameter Max (Metric)	25.0
-------------------------------------	------

Height H (Imperial)	1.53
----------------------------	------

Height H (Metric)

38.9

Depth D (imperial)

0.47

Depth D (metric)

12.0

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability

UL 94 HB

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

1000

Package Quantity (Metric)

1000

Content Unit(BMEcat)

pcs.

Weight (Metric)

3.84

Weight (Imperial)

0.14

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)