

Specification Sheet

Part Number: 156-01574



Head allows for a 0.2" lateral adjustment on stud during installation.

Quick and easy installation ideal for manufacturing environment.

2-Piece Cable Tie/Oval Stud Mount, 8.0" Long, 50lb Tensile, PA66HIRHSUV/POM, Black, 2000/ctn

Article Number	156-01574
Type	T50R0SBS6UM90SET
Color	Black (BK)
Quantity Per	bag
Product Description	Oval shaped stud mount's special design allows for a 0.2" (5.5mm) lateral adjustment in case of misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
Short Description	2-Piece Cable Tie/Oval Stud Mount, 8.0" Long, 50lb Tensile, PA66HIRHSUV/POM, Black, 2000/ctn
Global Part Name	T50R0SBS6UM90SET-PA66HIRHSUV/POM-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8
Length L (Metric)	203.2
Fixation Method	Stud Mount
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.52
Width W (Metric)	13.2
Bundle Diameter Min (Imperial)	0.16
Bundle Diameter Min (Metric)	4.0
Bundle Diameter Max (Imperial)	1.9
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.85
Height H (Metric)	21.50

Mounting Hole Diameter D (Imperial)	0.2 - 0.24
Mounting Hole Diameter D (Metric)	5.0 - 6.0 mm
Mounting Hole Diameter D Min (Imperial)	0.2
Mounting Hole Diameter D Max (Imperial)	0.24
Mounting Hole Diameter D Max (Metric)	6.0
Stud Diameter (Metric)	6.0 mm 5.0 mm
Stud Diameter (Imperial)	0.24 ", 0.20
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) Polyacetal (POM)
Material Shortcut	POM PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL 94 HB
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C) -22°F to +194°F (-30°C to +90°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	2000
Package Quantity (Metric)	2000
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)