

## Specification Sheet

Part Number: 156-01610



2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 8.9"L, 12mm Mounting Hole, PA66HIRHS, Black, 1000/ctn

**Article Number**

156-01610

**Type**

T120SFT12SET

**Color**

Black (BK)

**Features & Benefits**

- Robust fir tree design provides low insertion effort yet delivers exceptional retention strength in a 12 mm hole, for easy installation and reliable performance.
- Heavy Duty T120 tie provides a 120lb (534 N) tensile strength to secure bundles up to 2.2" (56 mm).
- Friction tab inside the fir tree allows the tie to sit in mount without falling out prior to installation.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

**Quantity Per**

carton

**Product Description**

These two-piece fasteners offer a simple and versatile method of bundling and mounting cables. Sold as an unassembled set, this oval fir tree and tie combination allows the user to install the tie in two different directions, securing the bundle perpendicular or inline to the oval mounting hole.

**Short Description**

2-Piece Cable Tie/Fir Tree Mount, Unassembled Set, 8.9"L, 12mm Mounting Hole, PA66HIRHS, Black, 1000/ctn

**Global Part Name**

T120SFT12SET-PA66HIRHSUV/PA66UV-BK

**Minimum Tensile Strength (Imperial)**

120.0

**Minimum Tensile Strength (Metric)**

535.0

**Length L (Imperial)**

0.89

**Length L (Metric)**

22.6

**Fixation Method**

Fir Tree

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.80

**Width W (Metric)**

20.40

**Bundle Diameter Min (Imperial)**

0.20

<b>Bundle Diameter Min (Metric)</b>	5.0
<b>Bundle Diameter Max (Imperial)</b>	2.17
<b>Bundle Diameter Max (Metric)</b>	55.00
<b>Height H (Imperial)</b>	1.17
<b>Height H (Metric)</b>	29.70
<b>Mounting Hole Diameter D (Imperial)</b>	0.47
<b>Mounting Hole Diameter D (Metric)</b>	12.0 mm
<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV PA66UV
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)