

## Specification Sheet

Part Number: 156-01640



2-Piece Cable Tie/Fir Tree Mount, 8.0" Long, 9–17 mm Mounting Hole, 50lb, PA66HS, Black, 3000/ctn

**Article Number**

156-01640

**Type**

T50RFT9X17A2

**Color**

Black (BK)

**Features & Benefits**

- 2-Piece assembled fir tree cable tie secures bundles running perpendicular to 9x17 oval mounting hole.
- Updated 9x17 mm oval fir tree design maintains bundle orientation.
- Fir tree provides low insertion force with high extraction resistance, for easy assembly and reliable performance.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

**Quantity Per**

carton

**Product Description**

These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables. The fir tree base will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be orientated to the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Short Description**

2-Piece Cable Tie/Fir Tree Mount, 8.0" Long, 9–17 mm Mounting Hole, 50lb, PA66HS, Black, 3000/ctn

**Global Part Name**

T50RFT9X17A2-PA66HS/PA66HIRHS-BK

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

8.0

**Length L (Metric)**

202.0

**Fixation Method**

Fir Tree for oval holes

**Identification Plate Position**

none

**Tie Closure**

plastic pawl

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.20

**Bundle Diameter Min (Metric)**

5.0

**Bundle Diameter Max (Imperial)**

2.0

<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Panel Thickness Min(Imperial)</b>	0.02
<b>Panel Thickness Max(Imperial)</b>	0.22
<b>Panel Thickness Min (Metric)</b>	0.6
<b>Panel Thickness Max (Metric)</b>	5.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.35 - 0.67
<b>Mounting Hole Diameter D (Metric)</b>	9.0 x 17.0 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	17.0
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Operating Temperature (Metric)</b>	-40°F to +230°F (-40°C to +110°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	3000
<b>Package Quantity (Metric)</b>	3000

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

0.002

**Weight (Imperial)**

0.005