

Specification Sheet

Part Number: 156-01641



2-Piece Cable Tie/Fir Tree Mount, 8.0" Long, 9–17 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 3000/ctn

Article Number

156-01641

Type

T50RFT9X17B2

Color

Black (BK)

Features & Benefits

- Updated 9x17mm oval fir tree design maintains bundle orientation.
- Fir tree provides low insertion force with high extraction resistance, for easy assembly and reliable performance.
- Disc feature prevents rattling in high-vibration applications and protects against debris ingress.

Quantity Per

carton

Product Description

These two-piece fasteners are pre-assembled and offer a simple and versatile method of bundling and mounting cables running perpendicular to 9x17 oval mounting holes. The fir tree base will easily push into pre-punched holes in panels or threaded blind holes and offers a secure fit. The two-piece design enables the head of the tie to be orientated to the required position to ease assembly, while the disc on top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description

2-Piece Cable Tie/Fir Tree Mount, 8.0" Long, 9–17 mm Mounting Hole, 50lb, PA66HIRHSUV, Black, 3000/ctn

Global Part Name

T50RFT9X17B2-PA66HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.0

Length L (Metric)

203.2

Fixation Method

Fir Tree for oval holes

Identification Plate Position

none

Tie Closure

plastic pawl

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial) 2.0

Bundle Diameter Max (Metric) 50.0

Panel Thickness Min(Imperial) 0.02

Panel Thickness Max(Imperial) 0.22

Panel Thickness Min (Metric) 0.6

Panel Thickness Max (Metric) 5.5

Mounting Hole Diameter D (Imperial) 0.35 - 0.67

Mounting Hole Diameter D (Metric) 9.0 x 17.0 mm

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Operating Temperature (Metric) -40°F to +221°F (-40°C to +105°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 3000

Package Quantity (Metric) 3000

Customs Number

3926909988

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.002

Weight (Imperial)

0.005