


## Specification Sheet

Part Number: 156-01693



Staggered fir tree branch design provides low insertion forces and high extraction forces.

Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Disc feature provides anti-rattle protection in high vibration applications.

2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .25 - .28" Mounting Hole Diameter, PA46, Gray, 500/pkg

Article Number 156-01693

Type T50RFT6

Color Gray (GY)

Quantity Per bag

**Product Description** HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

**Short Description** 2-Piece Cable Tie/Fir Tree Mount, 8.0"L, .25 - .28" Mounting Hole Diameter, PA46, Gray, 500/pkg

Global Part Name T50RFT6-PA46-GY

Minimum Tensile Strength (Metric) 225

Length L (Metric) 202

Fixation Method Fir Tree

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.16

Bundle Diameter Min (Metric) 4.0

Bundle Diameter Max (Imperial) 1.77

Bundle Diameter Max (Metric) 45.0

Thickness T (Metric) 1.2

Panel Thickness Min (Metric) 0.75

Panel Thickness Max (Metric) 3.0

Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
Mounting Hole Diameter D Max (Metric)	7.1
Disc Diameter (Metric)	16.0
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Material Cable Tie	Polyamide 4.6 (PA46)
Flammability	UL 94 V-2
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

