

Specification Sheet

Part Number: 156-01711



2-Pc Tie & Arrowhead Mnt w/ Seal, 0.6 - 1.1mm panel, 6.5mm/6.35mm HEX, PA66HIRHSUV/TPE, Black, 4000/ctn

Article Number 156-01711

Type T50RSRAH6.5SD

Color Black (BK)

Features & Benefits

- Once installed, perpendicular arrowhead arms reduce movement and will not collapse when exposed to water or load.
- Integrated dual seal meets IP65 for protection against water, dust, chemicals, air and sound.
- 15 mm and 25 mm offset designs fasten bundles away from obstructions, heat or sources of abrasion.
- Superior design and high-spec materials maintain routing position to deliver consistent performance in the most rugged applications.
- Low-profile design saves 5 mm of height when installed.
- All ties rated to 222 N (50 lb) tensile strength to ensure long-term bundling reliability.
- Sealed arrowhead meets USCAR44 push in, pull off and sealing standards.

Quantity Per	carton
Product Description	HellermannTyton sealed clips and ties are constructed of engineered nylon with a dual TPE (thermo plastic elastomer) seal. The combination of dual seal and engineered arrowhead provide superior sealing performance for applications where protection from moisture and debris is essential.
Short Description	2-Pc Tie & Arrowhead Mnt w/ Seal, 0.6 - 1.1mm panel, 6.5mm/6.35mm HEX, PA66HIRHSUV/TPE, Black, 4000/ctn
Global Part Name	T50RSRAH6.5SD-PA66HIRHSUV/TPE-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	200
Fixation Method	Arrowhead
Identification Plate Position	none
Tie Closure	plastic pawl
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.12

Bundle Diameter Min (Metric)	3.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.52
Height H (Metric)	13.25
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	1.1
Mounting Hole Diameter D (Imperial)	0.25 " (hexagonal) 0.25
Mounting Hole Diameter D (Metric)	6.5 mm 6.35 mm (hexagonal)
Material	Thermoplastic Elastomer (TPE) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV TPE
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes

Package Quantity (Imperial)	4000
Package Quantity (Metric)	4000
Customs Number	3926909988
Weight (Metric)	0.002
Weight (Imperial)	0.0044092452